



Standard Spec:

Adjustable spring disc coulter, narrow profile spring steel swivel legs (18mm) with wings and shear bolt protection and full width packer roller. Power requirement dependent on working depth 120 HP plus. Cat 2 & 3 linkage mounting overall width 2.8M. Adjustable tine angle. Hydraulic working depth adjustment. Full width slot closing flat ballast roller 460MM diameter. Can be ballasted.

Specification

Working Width:	2.8M	2.8M
Number of legs:	2	3
Power Requirement:	130HP	140HP
Leg Spacings*:	2M Leg Centres	1M Leg Centres

*Please note all legs have adjustable width



WEAVING

GRASSLAND SUBLIFT



Designed, developed and manufactured by ourselves at our Evesham base. The Weaving Grassland Sublift improves surface drainage by lifting the pan opening up the root zone, promoting earlier and more productive grass growth while leaving the sward surface virtually undisturbed due to its full width flat roller. Swivel legs allow the machine to be used in stoney conditions and reduces horse power requirement.

- Adjustable Spring Disc Coupler
- Narrow Profile Spring Steel Swivel legs
- Shear Bolt Protection
- Cat 2 & 3 Linkage Mounting
- 2.8M Overall Width
- Adjustable Tine Angle
- Hydraulic Working Depth Adjustment
- 460MM Diameter Flat Ballast Roller



Unique adjustable narrow winged legs



Serrated blades slice open the pan



Large flat ballast roller



Heavy duty box section chassis



Virtually undisturbed sward

