

# MegaCut



**2 YEAR WARRANTY**

## OVERVIEW

A combination of 3 mowers the MegaCut comprises of KDD 861 or 941 side mower mounted on joint linkage and KDF 300 front mower mounted on the tractors 3pl. Overlap of the front and side mowers is set to 375mm therefore mowing is faster and more effective.

## FEATURES

Road lights, PTO with over run protection, approach sensor, hydraulic breakaway device protection incase of striking an obstacle, adjustable front safety guards and folding side guards. Mechanical locking of cutting units whilst in transport position. The mower beds are equipped with perfect cut cutter bars, quick knife replacement and toolbox. Hydropneumatic suspension, electronic control.

## OPTIONS

Tine Conditioners, Rubber Swather Groupers

Specification	861	941
Working Width (m/ft)	8.6 / 28'2"	9.4 / 30'10"
Transport Width x Height (m/ft)	3.0 x 3.8 / 9'8" x 12'8"	2 x 2.3 x 2.7 / 2 x 7'7" x 8'10"
Swath Width (m/ft)	2 x 1.9 - 2.3 / 2 x 6'3" - 7.7"	2 x 2.3 - 2.7 / 2 x 7'7" - 8'10"
Necessary Hydraulic Couplers	3 x single acting (steering panel, 1 x single acting)	
Working Capacity (ac/hr)	25.0	27.0
Number of Discs / Knives	14 / 28	16 / 32
RPM	1000	1000
3-point Hitch Cat.	III	III
Power Demand (HP)	from 130	from 140
Weight (Kg)	2125	2290
PTO Shaft	tractor - mower: no clutch, built-in: with overrunning friction clutch	